

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 August 2005 (18.08.2005)

PCT

(10) International Publication Number
WO 2005/076602 A1

(51) International Patent Classification⁷: **H04N 5/64**,
F21V 33/00, H05B 37/02

(21) International Application Number:
PCT/IB2004/052750

(22) International Filing Date:
10 December 2004 (10.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
04100024.1 7 January 2004 (07.01.2004) EP

(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **OVERES, Theodorus, F., E., M.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). **VERHAGEN, Johannes, P., C., M.** [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agents: **GROENENDAAL, Antonius, W., M.** et al.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU,

[Continued on next page]

(54) Title: DISPLAY APPARATUS



(57) Abstract: The invention relates to a display apparatus with a display unit, having means for background lighting at the back of the display apparatus. According to the invention, the means for background lighting comprise two illumination units being provided at the right-hand and left-hand of the display apparatus, said illumination units being formed as substantially vertically positioned, longitudinal light guides comprising means for coupling out light, each of the light guides being provided on at least one of its ends with a light source. The light sources preferably comprise coloured LEDs.

WO 2005/076602 A1



*IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR),
OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG)*

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

Published:

— *with international search report*

Display apparatus

The invention relates to a display apparatus with a display unit, having means for background lighting at a side or the back of the display apparatus.

5 Such a display apparatus is known i.a. from the Utility Model publication DE 20002420. This publication discloses a simple back lighting system with limited back lighting possibilities.

 The present invention aims at providing an improved display apparatus. To this end, the invention provides a display apparatus as defined in claim 1. Devices having the
10 claimed features show a much greater impact on the viewer than the prior art display apparatus with the limited back lighting possibilities. This holds especially for display apparatus having a wide-screen display unit.

 The display apparatus according to the present invention has at least two illumination units, which are preferably attached to the back of the apparatus. In a preferred
15 embodiment of two units, the one unit is provided on the left-hand side of the apparatus and the other unit on its right-hand side. The units are formed as longitudinal light guides, preferably of a synthetic resin, like acrylic resin, which can be prepared by extrusion. The guides in principle can have a cross section of any desired shape, but preferably have a circular cross section. As the guides are positioned substantially vertical, they are attached to
20 the apparatus in a mutually parallel orientation. The display apparatus may have (an) additional illumination unit(s) on top and/or bottom side(s) of the display apparatus. Latter light guides are positioned substantially horizontal.

 The light guides employed in the display apparatus according to the present invention comprise means for coupling out light. It is possible to use a reflecting body
25 encapsulated in an extruded light guide. Preferably the means for coupling out light are formed as a structure provided on the surface of the light guide. This can be obtained by sandblasting part of the surface of the light guide according to a desired structure. Alternatively, good results are also obtained by printing a diffuse reflective layer on the surface of the light guide, or by applying it by means of a sticker. Under these circumstances,

it is preferred if the light guides contain a flat outer surface on which the desired structure can be applied.

It is noted that different structures for coupling out light from the light guide can be used. Seen in the length direction of the guide, the structure can be continuous or discontinuous ('zebra' or 'dotted' form). In case that one light source is used, the width of a continuous structure should increase at increased distance from the light source in order to obtain a continuous light output along the whole length of the light guide. In case that each of the light guides is provided with a light source at both of its ends, the width of the continuous structure will be maximal in the middle of the light guide in order to have the continuous light output along the length of the light guide. In case that a discontinuous pattern is used (stripes or dots), a continuous width of the stripes or dots with different pitch lengths between subsequent stripes or dots can be used in order to obtain the desired continuous light output.

An interesting display apparatus according to the present invention is characterized in that the light guides are rotatable along a longitudinal axis. This feature allows adjustment of the back lighting pattern on wall. This is particularly useful in case that the screen of the display apparatus is positioned not parallel to the back wall, but under a certain angle. In such situation, the user can rotate the light guides in such way that under operation of the back lighting a spot on the wall is obtained which is well balanced on both sides of the display apparatus. By means of this feature, the desired impact on the viewer is maintained, even when the display apparatus is positioned under an angle with respect to the back wall.

Another advantageous embodiment of the invented display is characterized in that the display apparatus comprises means for controlling the colour of the backlight and that the light guides are provided on both ends with a light source, said light source comprising a red, a green and a blue LED. By means of this embodiment, the display unit may produce light, the colour and light intensity of which can be adapted in order to fit optimally with the colour of the room in accordance with the wishes of the user.

Interesting is also the embodiment which is characterized in that the display apparatus comprises a control circuit for controlling the colour of each of the light sources in dependence of a colour of a part of the display screen which is close to the light source. With display apparatus having this feature seem to project an additional part of the scene displayed on the apparatus in a dynamic way on the back wall. It has been shown that the dynamic spot displayed on the wall induces an extraordinary great impact on the viewer, as in this way the scene observed seems to be increased.

These and other aspects of the invention will be apparent from and elucidated with reference to the embodiments described hereinafter and a drawing, in which:

5 Figure 1 shows an embodiment of a display apparatus according to the present invention;

Figure 2 shows a schematic top view of the display apparatus according to the invention as shown in Figure 1;

10 Figure 3 shows a detail of the display apparatus according to the invention as depicted in Figure 1;

Figure 4 shows a block diagram of a first embodiment of a control circuit for use in a display apparatus according to the invention;

Figure 5 shows another embodiment of a display apparatus according to the present invention.

15 The Figures are purely diagrammatic and not drawn true to scale. Dimensions may be exaggerated for reasons of clarity. In the Figures equivalent parts have been given as much as possible the same reference number.

20 The display apparatus (1) as shown in Figures 1 and 2 is preferably mounted by mounting means (2) to a wall (3) of a room. According to the present invention, attached to its back, the display apparatus comprise two illumination units (4) for providing a background light formed as two spots (5) on wall (3). These spots (5) are displayed at the left-hand side and the right-hand side of the display apparatus. Usually they are only
25 displayed during operation of the display apparatus. However it is also possible to display them during the time that the display apparatus is switched off.

Figure 3-A shows a front view of an illumination unit (4), which can be used in the display apparatus according to the present invention. The unit comprises longitudinal light guide (6) having a cylindrical form. The surface of the unstructured light guide is
30 polished in order to prevent coupling out of light inserted in the guide during operation. In the present case, the light guide is made of an acrylic resin (PMMA, poly-methyl-methacrylate) by means of extrusion. On a flat part of its surface, a longitudinal structure (7) is prepared by means of printing. This structure causes that part of the light being inserted in the guide is coupled out. Light can be coupled in at a flat end (8) of the light guide by means

of light source (9). This light source can be an incandescent lamp or a halogen lamp. However, it is preferred to use one or more LEDs (10) for this purpose. In the present embodiment the light source consists of a set of three LEDs (10), the individual LEDs emitting Red, Blue and Green light.

5 During operation of the illumination unit (4), a certain amount of light enters the light guide (6) generated by LEDs (10) via flat end (8). By means of longitudinal structure (7) part of the inserted light is coupled out of the light guide in a direction substantially perpendicular to the longitudinal axis of the light guide (6). In order to keep the amount of light coupled out substantially constant over the whole length of the guide, the
10 width of the coupling out structure increases as the distant from the light source to the coupling out area increases.

 Figure 3-B shows an alternative illumination unit (4), which comprises two light sources (9) per light guide (6). Again in this example the use of LEDs as light source are preferred over the use of alternative light sources. In order to achieve a constant out coupling
15 of light during operation of the light guide, the width of the applied coupling out structure is maximal in the middle of the light guide.

 Figure 3-C shows another alternative illumination unit (4), which comprises a single light source (6) having a single Blue LED (10). In this example a discontinuous, zebra-like coupling out structure (7) is used in order to keep the light output constant along the the
20 length of the light guide. This structure is prepared by sandblasting the desired lines of the coupling out structure in the coupling out light guide. In this embodiment, the lines have equal width and equal length. The person skilled in the art can of course design alternative structures in which the lines have different length and widths and in which the distance between neighbouring lines are adjusted to these alternative structures.

25 In general, the structure is applied in such way that the light beam coupled out from the light guide emits under an angle of 50 – 90 degrees. An optimal effect is however reached in case that said angle is 70 degrees with a deviation of maximally 10 degrees, preferably 5 degrees.

 Returning to Figure 2, it is stressed that the illumination units (4) can be
30 rotated along the longitudinal axis of the light guides, as indicated by the arrows. In case that the display apparatus is positioned under an angle with respect to the wall (i.e. the plane of the screen of the display apparatus is not parallel to the plane of the wall), the light spots (5) displayed on the wall during operation of the apparatus can be adjusted manually by the user in order to give them an optimal shape. This holds both for TV-sets or monitors that are

attached to the wall and for apparatus standing free of the wall. In practise the light guides can be clamped in one or more settings, which allows rotation of the guides along their longitudinal axis.

The display indicated comprises means for controlling the colour of the backlight. The colour produced by the illumination unit of a display apparatus without such controlling means can be neutral white or a static colour. However it is preferred that the illumination unit produces during operation coloured light, the wavelength and brightness of which can be adjusted by the user according to his wishes. To this end, the display apparatus has a control unit CU that produces red, green and blue control signals RCS, GCS, BCS that control red, green and blue LEDs (10) of the illumination units (4). The control unit CU receives a user control signal UCS (that may be produced by a remote control signal reception device) to set the colour in such a manner that it fits in with the wish of the user. A block diagram for this embodiment is shown in Figure 4. While the illumination unit preferably employs LEDs, other light sources may also be used instead in alternative embodiments. The control unit may receive a signal from a light sensor so as to make the light from the illumination unit dependent on ambient light as well.

Figure 5 shows a further interesting embodiment of a display according to the present invention, which is characterized in that the display apparatus comprises a control circuit for controlling the colour of each of the light sources in dependence of a colour of a part of the display screen, which is close to the light source. More particularly it shows a front view of a display apparatus (1) with a display screen (11) and two illumination units (4) on the left-hand and the right-hand side of the apparatus. Each of the illumination units (4) comprises a longitudinal light guide with a light source (9) on each of both ends of the light guides. Said light sources are composed of three LEDs emitting blue, green and red light.

The display apparatus also comprises a circuit for controlling the colour of the light sources. To this end, the display apparatus has a control unit CU that produces red, green and blue control signals RCS, GCS, BCS that control the average colour produced by the red, green and blue LEDs (10) of one of the four light sources of the two illumination units (4). The control unit CU receives a control signal UCS to set the colour of one of the light sources, which signal is dependent on the average colour of one of the segments (12), (13), (14) or (15) of screen (11) or of a part thereof. Thus the produced colour of the light source of each of the four light sources is dependent on the average colour of the segment, which is closest to the light source. It is stressed that not only an average colour can be selected in this way, but also a dominant colour, this all upon the wish of the user.

Due to colour mixing in the longitudinal light guides, a smooth colour transition between both ends of the light guides is obtained. Thus in case of a picture of the beach, both top segments 12 and 13 are essentially blue and the light sources on top of both light guides will produce essentially blue light. Both bottom segments are however
5 essentially yellow, and the light sources on bottom of both light guides will produce essentially yellow light. In the light guides a transition from top (blue) to bottom (yellow) is obtained for such picture. This colour transition is displayed on the wall. It appears that this kind of dynamic back lighting in a display causes a very impressive impact on the viewer. It essentially broadens the width of the scene displayed on the display apparatus.

10 It should be noted that the above-mentioned embodiments illustrate rather than limit the invention, and that those skilled in the art will be able to design many alternative embodiments without departing from the scope of the appended claims. In the claims, any reference signs placed between parentheses shall not be construed as limiting the claim. Use of the verb 'comprise' and its conjugations does not exclude the presence of elements or steps
15 other than those stated in a claim. The article 'a' or 'an' preceding an element does not exclude the presence of a plurality of such elements. The invention may be implemented by means of hardware comprising several distinct elements and by means of a suitable programmed computer. In the device claim enumerating several means, several of these means may be embodied by one and the same item of hardware. The mere fact that certain
20 measures are recited in mutually different dependent claims does not indicate that a combination of these measures cannot be used to advantage.

CLAIMS:

1. A display apparatus with a display unit, having means for background lighting at a side or the back of the display apparatus, characterized in that the means for background lighting comprise two illumination units being provided at the right-hand and left-hand of the display apparatus, said illumination units being formed as substantially vertically positioned,
5 longitudinal light guides comprising means for coupling out light, each of the light guides being provided on at least one of its ends with a light source.
2. A display apparatus according to claim 1, characterized in that the means for coupling out light are formed as a structure provided on the surface of the light guide.
10
3. A display apparatus according to claim 2, characterized in that the light guides are rotatable along a longitudinal axis.
4. A display apparatus according to claim 1, characterized in that the display
15 apparatus comprises means for controlling the colour of the backlight and that the light guides are provided on both ends with a light source, said light source comprising a red, a green and a blue LED.
5. A display apparatus according to claim 4, characterized in that the display
20 apparatus comprises a control circuit for controlling the colour of each of the light sources in dependence of a colour of a part of the display screen which is close to the light source.

1/3

1/3




FIG.1

2/3

2/3




FIG. 2




FIG. 4




FIG. 5

3/3

3/3




FIG. 3A




FIG. 3B




FIG. 3C

INTERNATIONAL SEARCH REPORT

International Application No
PCT/IB2004/052750

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04N5/64 F21V33/00 H05B37/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 H04N F21V H05B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	FR 1 323 696 A (ETABLISSEMENTS INDUSTRIELS D. SOULE) 3 July 1963 (1963-07-03) column 1 figure 1	1-4
Y	US 2003/123245 A1 (PARKER JEFFERY R ET AL) 3 July 2003 (2003-07-03) abstract paragraph '0050! - paragraph '0051! paragraph '0057! paragraph '0066! figure 43	1-3
Y	DE 42 07 417 A1 (AMSBECK, KLEMENS, 83620 FELDKIRCHEN-WESTERHAM, DE) 16 September 1993 (1993-09-16) column 1, line 20 - line 30 claim 1	4
	-/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

26 January 2005

Date of mailing of the international search report

24/02/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Bouba1, F

INTERNATIONAL SEARCH REPORT

International Application No
PL 1 / IB2004/052750

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 36 29 593 A1 (OTT,ELMAR,DIPL.-ING) 5 March 1987 (1987-03-05) column 2, line 16 - line 27 column 3, line 39 - line 42 figure 5 -----	1,3

INTERNATIONAL SEARCH REPORT

 International Application No
 PCT/IB2004/052750

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 1323696	A	03-07-1963	NONE	
US 2003123245	A1	03-07-2003	US 2002141174 A1	03-10-2002
			US 6079838 A	27-06-2000
			US 5613751 A	25-03-1997
			AU 3499300 A	14-09-2000
			EP 1163473 A1	19-12-2001
			JP 2002538577 A	12-11-2002
			WO 0050807 A1	31-08-2000
			US 6827456 B2	07-12-2004
			US 2002080598 A1	27-06-2002
			US 2003007344 A1	09-01-2003
			US 2003123246 A1	03-07-2003
			US 2003123247 A1	03-07-2003
			US 2003202338 A1	30-10-2003
			US 2004012946 A1	22-01-2004
			US 2004085749 A1	06-05-2004
			US 2004080927 A1	29-04-2004
			US 2004114346 A1	17-06-2004
			US 2004135273 A1	15-07-2004
			US 2004165372 A1	26-08-2004
			US 2001053075 A1	20-12-2001
			US 2005007759 A1	13-01-2005
			US 6185356 B1	06-02-2001
			US 2001001260 A1	17-05-2001
			US 5975711 A	02-11-1999
			US 2002058931 A1	16-05-2002
			DE 69608499 D1	29-06-2000
			DE 69608499 T2	18-01-2001
			EP 0751340 A2	02-01-1997
			JP 9021916 A	21-01-1997
			US 5618096 A	08-04-1997
			US 5921652 A	13-07-1999
			US 5876107 A	02-03-1999
DE 4207417	A1	16-09-1993	NONE	
DE 3629593	A1	05-03-1987	DE 3629592 A1	05-03-1987